

CORDIN

SCIENTIFIC IMAGING

HIGH SPEED ROTATING MIRROR STREAK CAMERA

Model 131-HD

- **Very high spatial resolution**, 6400 pixels
- **Fast temporal resolution**, down to 650 ps
- **Software control** of exposure and timing parameters
- **Laser and pulsed flash illumination synchronization**
- **Long record length**, up to 46,000 pixels
- **Re-triggerable within seconds**
- **14 bit image depth**
- **Programmable time delay functions**
- **Captures external electronic fiducial inputs** on common time base
- **Electronic shuttering** prevents image overwrite



The **Cordin Model 131-HD** camera is the ideal analytical tool for continuously measuring one dimension over time for a given event. The rotating mirror architecture provides long record length and recording rate flexibility. Combining rotating mirror and CCD technology provides users with access to digital streak image information in seconds. This allows the researcher to record data ready for subject adjustment, analysis, or presentation. A unique opto-mechanical design provides a continuous digital streak record, without gaps, blemishes, and with negligible distortion.

The Model 131-HD streak image is 6400 pixels in the spatial axis, and 17,000 pixels along the temporal axis. Optional extended record configurations offer up to 46,000 pixels on the temporal axis.

The Model 131-HD is offered with two alternative rotating mirror turbines: the standard 1209 turbine operates to 5,000 rps and the optional 1231 turbine operates to 7,500 rps. The turbines can reach 50% of full speed using compressed air or nitrogen. Helium is required to reach full speed.

The writing rate is determined by the speed of the rotating mirror, which is software controlled. At top speed, using the 1209 turbine the recording rate is 4,460 pixels per microsecond. The 1231 turbine at top speed yields a recording rate of 6,700 pixels per microsecond.

Two fiducial inputs are provided for precise image synchronization. Two programmable delayed outputs are also provided. An intuitive PC-based user interface allows for easy setup, acquisition, alignment, analysis and saving of data.

OPTIONS

Extended record length to 46,000 pixels

High speed turbine (Model 1231)

Optical fiducial mark generator

Custom objective optics

Custom slit configurations


Laser field of view alignment tool

CORDIN

SCIENTIFIC IMAGING

Model 131-HD

HIGH SPEED ROTATING MIRROR STREAK CAMERA



Screen shot of the Model 131-HD user interface

SPECIFICATIONS

Record Width	6400 pixels	Data Interface	Gigabit Ethernet
Record Length	17,000 pixels standard	Trigger Inputs	+5V, +5V isolated, analog and optical with threshold
Extended Track Length	21,000, 34,000 or 46,000 pixels <i>optional</i>	Fiducial Inputs	Two independent channels captured on common time base
Minimum Temporal Feature	4.5 pixels at 25 micron slit width	Delay Outputs	Two programmable delay channels on common time base
ADC Dynamic Range	14 bit		
Radius of Image Arc	400 mm		
Subtended Angle of Arc	13 degrees standard, 37 degrees maximum		
Objective Lens	Nikon F-mount standard Other objective optics available	Turbine	MODEL 1209 MODEL 1231
Pixel Size	5.5 x 5.5 microns	Max Mirror Rotation	5000 rps 7500 rps
Device Type	29 MPixel full resolution progressive scan Black and white standard	Temporal Resolution	1.0 ns 0.65 ns
		Record Length	
		17,000 Pixel Configuration	3.8 µsec 2.6 µsec
		46,000 Pixel Configuration	10.2 µsec 7.0 µsec

